




CODE EA 1346



LUMINAIRE SPECIFICATION

MAKE	eAge Electronics Pvt Ltd
DESCRIPTION	DOWN LIGHT
LUMEN	393 / 410 / 592 LM
FIXED	YES
ADJUSTABLE ANGLE	NO
ROTATABLE ANGLE	NO
DIFFUSER	REFLECTOR AND LENS
UGR	≤ 10
PROTECTION	IP 44

LAMP

TECHNOLOGY	LED
MAKE	CREE / TRIDONIC
WATTAGE (W)	5W
CRI	≥80
CCT	2700K / 3000K / 4000K / 5000K
BEAM DISTRIBUTION	20° /30°/50°
LAMP LIFE	40,000HRS
MacAdam	≤3 SDCM

LUMINAIRE DIMENSIONS

DIAMETER	70 MM
HEIGHT	36 MM
CUT-OUT	55 MM

DRIVER

MAKE	BAG /OSRAM / PHILLIPS/ LITECH
POWER SUPPLY	REMOTE LED DRIVER
CONTROL	ANALOG
DIMMABLE DRIVER	DIMMABLE / NON-DIMMABLE
DIMMING PROTOCOLS	TRIAC DIM/ DALI DIM/ 1-10V DIM
INPUT-VOLTAGE	85-305V AC
OUTPUT - VOLTAGE	12V DC
OUTPUT - CURRENT	500mA
POWER FACTOR (PF)	≥0.9 %
THD	≤ 10%
DRIVER IP PROTECTION	IP20



SPECIAL FEATURES

LUMINAIRE HOUSING

MATERIAL	ALUMINIUM PRESSURED DIE CAST
FINISH	WHITE/BLACK

ACCESSORIES

HONEYCOMB LOUVER	NA
MOUNTING ACCESSORIES	NA

SPECIAL REQUIRMENTS



