




CODE EA 1347



LUMINAIRE SPECIFICATION

| | |
|------------------|--------------------------|
| MAKE | eAge Electronics Pvt Ltd |
| DESCRIPTION | DOWN LIGHT |
| LUMEN | 477 / 518 / 490 LM |
| FIXED | YES |
| ADJUSTABLE ANGLE | NO |
| ROTATABLE ANGLE | NO |
| DIFFUSER | REFLECTOR AND LENS |
| UGR | ≤ 10 |
| PROTECTION | IP 44 |

LAMP

| | |
|-------------------|-------------------------------|
| TECHNOLOGY | LED |
| MAKE | CREE / TRIDONIC |
| WATTAGE (W) | 7W |
| CRI | ≥80 |
| CCT | 2700K / 3000K / 4000K / 5000K |
| BEAM DISTRIBUTION | 20° /30°/50° |
| LAMP LIFE | 40,000HRS |
| MacAdam | ≤3 SDCM |

LUMINAIRE DIMENSIONS

| | |
|----------|-------|
| DIAMETER | 70 MM |
| HEIGHT | 36 MM |
| CUT-OUT | 55 MM |

DRIVER

| | |
|----------------------|--------------------------------|
| MAKE | BAG /OSRAM / PHILLIPS/ LTECH |
| POWER SUPPLY | REMOTE LED DRIVER |
| CONTROL | ANALOG |
| DIMMABLE DRIVER | DIMMABLE / NON-DIMMABLE |
| DIMMING PROTOCOLS | TRIAC DIM/ DALI DIM/ 1-10V DIM |
| INPUT-VOLTAGE | 85-305V AC |
| OUTPUT - VOLTAGE | 12V DC |
| OUTPUT - CURRENT | 500mA |
| POWER FACTOR (PF) | ≥0.9 % |
| THD | ≤ 10% |
| DRIVER IP PROTECTION | IP20 |



SPECIAL FEATURES

LUMINAIRE HOUSING

| | | | |
|----------|------------------------------|----------------------|----|
| MATERIAL | ALUMINIUM PRESSURED DIE CAST | HONEYCOMB LOUVER | NA |
| FINISH | WHITE/BLACK | MOUNTING ACCESSORIES | NA |

ACCESSORIES

SPECIAL REQUIRMENTS

