


CODE EA 1351



LUMINAIRE SPECIFICATION

MAKE	<u>eAge Electronics Pvt Ltd</u>
DESCRIPTION	DOWN LIGHT
LUMEN	700 / 718 / 690 / 702 LM
FIXED	NO
ADJUSTABLE ANGLE	YES (50°)
ROTATABLE ANGLE	YES
DIFFUSER	REFLECTOR AND LENS
UGR	≤ 10
PROTECTION	IP 20

LAMP

TECHNOLOGY	LED
MAKE	CREE / TRIDONIC
WATTAGE (W)	8W
CRI	≥80
CCT	2700K / 3000K / 4000K / 5000K
BEAM DISTRIBUTION	15° / 25° / 38° / 60°
LAMP LIFE	40,000HRS
MacAdam	≤3 SDCM

LUMINAIRE DIMENSIONS

DIAMETER	95 MM
HEIGHT	45 MM
CUT-OUT	83 MM

DRIVER

MAKE	BAG /OSRAM / PHILLIPS/ LITECH
POWER SUPPLY	REMOTE LED DRIVER
CONTROL	ANALOG
DIMMABLE DRIVER	DIMMABLE / NON-DIMMABLE
DIMMING PROTOCOLS	TRIAC DIM/ DALI DIM/ 1-10V DIM
INPUT-VOLTAGE	85-305V AC
OUTPUT - VOLTAGE	12V DC
OUTPUT - CURRENT	500mA
POWER FACTOR (PF)	≥0.9 %
THD	≤ 10%
DRIVER IP PROTECTION	IP20



SPECIAL FEATURES

ROTATABLE ANGLE	HORIZONTAL 360°
-----------------	-----------------

LUMINAIRE HOUSING

MATERIAL	ALUMINIUM PRESSURED DIE CAST	HONEYCOMB LOUVER	NA
FINISH	WHITE/BLACK	MOUNTING ACCESSORIES	YES

ACCESSORIES

SPECIAL REQUIRMENTS



