




CODE EA-5571210-10



LUMINAIRE SPECIFICATION

MAKE	eAge Electronics Pvt Ltd
DESCRIPTION	RECESS ADJUSTABLE DOWNLIGHT
LUMEN	359 / 436 / 483 / 562 / 668 / 697 / 837 LM/W
FIXED	NO
ADJUSTABLE ANGLE	YES
ROTATABLE ANGLE	YES (350°)
DIFFUSER	REFLECTOR AND LENS
UGR	≤ 10
PROTECTION	IP 20

LAMP

TECHNOLOGY	LED
MAKE	CREE/ BRIGRLUX/ NICHIA
WATTAGE (W)	7W/8W/10W/ 12W/ 15W
CRI	≥90
CCT	2700K/3000K/4000K
BEAM DISTRIBUTION	15° / 28° / 38° / 55° / 8°
LAMP LIFE	40,000HRS
MacAdam	≤3 SDCM

LUMINAIRE DIMENSIONS

DIAMETER	107*107 MM
HEIGHT	104 MM
CUT-OUT	100*100 MM

DRIVER

MAKE	BAG /OSRAM / PHILLIPS/ LTECH
POWER SUPPLY	REMOTE LED DRIVER
CONTROL	ANALOG
DIMMABLE DRIVER	DIMMABLE / NON-DIMMABLE
DIMMING PROTOCOLS	TRIAC DIM/ DALI DIM/ 1-10V DIM
INPUT-VOLTAGE	85-305V AC
OUTPUT - VOLTAGE	12V DC
OUTPUT - CURRENT	500mA
POWER FACTOR (PF)	≥0.9 %
THD	≤ 10%
DRIVER IP PROTECTION	IP20



SPECIAL FEATURES

LUMINAIRE HOUSING

MATERIAL	ALUMINIUM PRESSURED DIE CAST	HONEYCOMB LOUVER	YES
FINISH	WHITE/BLACK	MOUNTING ACCESSORIES	YES

ACCESSORIES

SPECIAL REQUIRMENTS

